

HUNTONIT

FDV - 010

Product: Antique Ceiling Roll/Brush Painted
Format: 11 x 620 x 1220 mm

Areas of Use	
Areas of Use Mounting	Can be used on all ceilings in residential areas, including wet rooms. A normal height of 2.4 m and suitable ventilation are required for wet rooms. Mounted on electrical lath, or directly across dry joists or lath.dry beams/laths. Then with the end joint on the beam. All free edges must be supported with nailing strips.
Nails	1.7/25 with head
Tie type	≥ 10 mm back and corresponding capacity
Painting	Acrylic paint YL. group 00
Screw type wood/metal	BK25 Christiania Spigerverk, or equivalent
Distance of fastening points	Mounted lengthwise on laths: CC 15–20 cm. Mounted across laths/beams: 2 per intersection and 4 in the end joint
Dealer	
Name	Huntonit AS
Address	PO Box 21, 4701 Vennesla, Norway
Telephone	381 37100
Fax	381 37101
Website	http://www.huntonit.no
E-mail	byggma@byggma.no
Contact person	Product Manager
Product Description	
Designation	White ceiling panels with smooth surface
Format	11 x 620 x 1220
Colors	NCS S 0502 Y (White) and NCS S 0500-N (Brilliant White)
Glossiness	20
Maintenance painting	Clean before painting with approved interior paints
Fire classification	D-s2, d0 in accordance with NS-EN 13501-1
Cleaning	Washable with damp cloth. Do not steam clean
Degassing	No harmful emissions to the indoor environment. Conf: NBI 571.04
Notes	
Indoor storage	Store in dry conditions. Acclimate in the packaging before use
Wallpaper paste	When wallpapering, any paste that gets on the ceiling must be washed off immediately. Wallpaper paste acts as a slow-acting paint remover
Shaping	Cut with a saw. Suction on saw is recommended
Acclimating	Acclimating in the packaging to room temperature
Asthma Allergies	Recommended by the Norwegian Asthma Allergy Association. NAAF
Fire classification	D-s2, d0 in accordance with NS-EN 13501-1
Construction site environment	All masonry and sanding work must be completed before the panels are removed from the packaging and installed. Temperature ≥ 12 degrees C. Relative humidity ≤ 65%
Approval	TG 2038 (from SINTEF Certification)

Modified: 01/06/2024

Replaces: 03/17/2017

BYGGMA
group