

# HUNTONIT

FDV – 039

**Product: Huntonit Brush Painted/Roller Painted Wall Panel:  
Shadow, Pearl, Microfuge and Fascia Panels  
Format: 11 x 620 x 2390/2740**

Areas of Use	
	Climate class 2 walls. Can be used in "dry zones" in wet rooms.
Mounting	In wood/metal studs/nailing strips cc.600
Nail type	1.7 x 35 pin
Tie type	≥ 10 mm back and corresponding capacity
Screw type wood/metal	BK.25. Christiania Spigerverk or equivalent
Bonding on metal studs	PL 400/Superfix or equivalent. Bonding to metal studs with: "LIM-O-TETT-Bostik" plus 4 screws at floor height
Distance of fastening points	15 cm. nails/ties. 40 cm in nail plug
Dealer	
Name	Huntonit AS
Address	PO Box 21, 4701 Vennesla, Norway
Telephone	381 37100
Fax	381 37101
Internet address	<a href="http://www.huntonit.no">http://www.huntonit.no</a>
E-mail	<a href="mailto:byggma@byggma.no">byggma@byggma.no</a>
Contact person	Kjell Torland, Product Manager.
Product Description	
Designation	Pre-painted wall panels with profiled surface.
Paint type	Acrylic paint. YL group 00 Manufacturer: F-Steen Hansen Paint Factory, Bergen
Color/glossiness	Various colors Glossiness 20
Indoor climate	Recommended by the Norwegian Asthma and Allergy Association
Maintenance	Clean before painting with approved interior paints. A pure acrylic paint must be used, which gives the best adhesion to the underlayer.
Cleaning	Washable with damp cloth. Do not steam clean.
Notes	
Conditioning	Painted panels must not be aired out. Remove straight from the packaging
Indoor storage	Store in dry conditions. Acclimate/temper in the packaging before use.
Shaping	Cut with a saw. Suction on saw is recommended.
Fire classification	K <sub>2</sub> 10 D-s2, d0 in accordance with NS-EN 13501-1
Construction site environment	All masonry and plastering work must be completed before the panels are installed
Approvals	TG 2038 (from SINTEF Certification)

Modified: 01/06/2018

Replaces: 01/06/2024